

TECHNICAL SPECIFICATION



Applications:

- Designed to meet the 10Gb/s Transmission.
- Digital Video
- High-Speed application like Data Center Cabling

Part Number	Item Number
V622410	Category 6A Patch Panel

Material	
Front Plate	Fireproof ABS UL-94V0
Panel	Metal (SPCC)
Cable Management	Metal (SPCC)
Shield	Galvanized steel
Grounding Cable	1.5mm PVC jacket
Packing Material	PE

Electrical Specification	
Insulation Resistance	500M Ohm (min)
Contact Resistance	20m Ohm (Max)
Current Rating	1.5 Amps
DC Resistance	0.1 Ohms (Max)
Withstanding Voltage	1000 VAC RMS @ 60Hz /1 min

Description:

24 Modules with keystone fitting
 Patch Panel is configurable with Cat.6 & Cat.6A
 Patch Panel fits standards 19" EIA rack mount widths
 Pre-installed grounding set



Grounding set



Grounding set

Accessories:



Blank Module:

Part Number	Item Number
V622000	Blank Module

Specification	
Body	Fire Proof ABS, UL-94V0
Operation Temp.	-40°C to +70°C
Color	White

Description:

Unused port of the Patch Panel (24 Port) can be filled by Blank Module provided. It is easily fitted into the patch panel.

Packing
One unloaded, 100 present shielded panel with Grounding cable in a protector PE. 6 Pcs of blank Module, Cable tie, label for marking and cover. All packed in a labeled box.